

## AS 504 - Technical Specifications



### Description

AS 504 is an agro-industrial tire mainly designed for soil tillage, implement and material-handling operations. This tire, which features excellent self-cleaning properties and increased grip, is suitable for field trailers and telehandlers. AS 504 is available in several versions to meet specific end-user requirements: an "HD" version with a special cut-and-chip resistance compound, while the "special" version has a reinforced casing that ensures a longer tire life.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Telehandler • Field Trailer

Industrial: Telehandler

Version	STANDARD
Type	TL
Tyre Size	15.5/80 - 24
LI/SS DRIVE WHEEL	142 A8
LI/SS FREE ROLLING	154 A8

## Dimensions International Standard

Ply Rating	10
Section Width (mm)	384
Overall Diameter (mm)	1262
Static Loaded Radius (mm)	570
Rolling Circumference (mm)	3875
SRI (mm)	600
Rim Rec	W 12
Rim Alt	W 13 ; W 14 L
ECE	E11-106R-004349

## Load capacity (Kg)

	km/h / bar	2.50
	10 FR	5250
	25 FR	4465
	30 FR	4200
	40 FR	3750
	10 DW	3710
	25 DW	3155
	30 DW	2970
	40 DW	2650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 08/11/2024 09:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..