



AS 511 - Data Sheet

Description

AS 511 is best suited for grassland operations with implement machinery. The robust casing and the special cut-resistant tread compound ensure extraordinary stability plus enhanced performance. Thanks to its large contact area, AS 511 ensures excellent traction and minimizes soil compaction.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Implement Machinery



SIZE	Version	USACode	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
31 X 15.50 R 15	STANDARD	94059782	13 LB		15.3	30.9	13.9	94	TL	E11-106R-005098

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 08/11/2024 09:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..