

DESERT KING - Technical Specifications



Description

DESERT KING is best suited for loose soil, sandy terrain and paver applications with desert trucks. The optimized rib tread design offers excellent flotation and directional stability. Its strong nylon casing and heavy-duty bead are specially developed for low pressure operations. DESERT KING provides also high punctures resistance and a longer tire life.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Desert Truck

Version	STANDARD
Type	TL
Tyre Size	29.5 - 25 DT

Dimensions International Standard

Ply Rating	28
Section Width (mm)	770
Overall Diameter (mm)	1822
Static Loaded Radius (mm)	786
Rolling Circumference (mm)	5392
Rim Rec	25.00/3.5
TRA Code	E7

Load capacity (Kg)

km/h / bar	2.50
10	13200
50	10000
65	8250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 08/11/2024 04:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..