

## EARTHMAX SR 331 - Data Sheet



### Description

EARTHMAX SR 331 is the BKT new multi-block tread pattern tire specially engineered and designed for multi-purpose trucks and Emergency Response vehicles. The unique tread pattern is essential to maximize ground contact and therefore guarantees excellent handling and comfort in all conditions. This non-directional tire has extraordinary self-cleaning properties. EARTHMAX SR 331 has been designed by BKT to excel in flotation and traction, essential requirements to operate effectively on soft, sandy and muddy soils. Extended durability is ensured by its All Steel strong casing and belt package, which also provide outstanding resistance to snags and punctures.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Universal Vehicle

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	ECE
24 R 21	STANDARD	94067671	176 G	18.00		23.9	54.4	24.7	165.1	TL	E11-54R-0019350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 08/11/2024 09:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..