

## EARTHMAX SR 45 M - Data Sheet

### Description

EARTHMAX SR 45 M is an **All Steel** radial tire specially designed for rigid haul trucks. EARTHMAX SR 45 M provides optimum traction and is ideal for operation in long hauls.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Rigid Dump Truck



SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth	TKPH
18.00 R 33	CUT RESISTANT COMPOUND	E4	***	195 B	13.00/2.5		505	1870	856	5608	TL	55	185
18.00 R 33	CUT RESISTANT COMPOUND	E4	**	191 B	13.00/2.5	--	505	1870	856	5608	TL	55	185
18.00 R 33	HEAT RESISTANT COMPOUND	E4	**	191 B	13.00/2.5	--	505	1870	856	5608	TL	55	256
18.00 R 33	STANDARD COMPOUND	E4	***	195 B	13.00/2.5		505	1870	856	5608	TL	55	220
18.00 R 33	STANDARD COMPOUND	E4	**	191 B	13.00/2.5	--	505	1870	856	5608	TL	55	220
24.00 R 35	CUT RESISTANT COMPOUND	E4	**	209 B	17.00/3.5	--	664	2180	980	6538	TL	70	333
24.00 R 35	HEAT RESISTANT COMPOUND	E4	**	209 B	17.00/3.5	--	664	2180	980	6538	TL	70	435
24.00 R 35	STANDARD COMPOUND	E4	**	209 B	17.00/3.5	--	664	2180	980	6538	TL	70	390

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 14/03/2025 14:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..