

# EARTHMAX SR 50 - Technical Specifications



## Description

EARTHMAX SR 50 (L-5) is an **All Steel** radial tire specially designed for loaders. The durable casing and sidewall protectors are ideal for the most demanding operations. EARTHMAX SR 50 is made of a special cut-resistant compound which ensures a long wear life. Operators will also appreciate its excellent traction, stability and comfortable ride.

## UM

International Standard

## Construction

 RADIAL

## Machinery

OTR: Loader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 25
LI/SS	216 A2

## Dimensions International Standard

Overall Width (mm)	775
Overall Diameter (mm)	1901
Static Loaded Radius (mm)	862
Rolling Circumference (mm)	5722
Rim Rec	25.00/3.5
Star Rating	**
TRA Code	L5

## Load capacity (Kg)

km/h / bar	5.25	5.50	5.75	6.00	6.25	6.50
10	19000	19500	20000	20600	21200	22400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 08/11/2024 11:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..