

## MP 600 - Technical Specifications



### Description

MP 600 is an agro-industrial tire, suitable for municipality/maintenance operations with telehandlers and implement machinery, providing a comfortable driving experience. This tire provides good traction and excellent self-cleaning properties along with an extended product life-cycle.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Implement Machinery • Telehandler  
Industrial: Telehandler • Universal Vehicle

Version	STANDARD
Type	TL
Tyre Size	400/70 - 24 (16.0/70 - 24)
LI/SS DRIVE WHEEL	158 A8

## Dimensions US Standard

Usa code	94049318
Ply Rating	18
Section Width (inch)	15.9
Overall Diameter (inch)	46.7
Static Loaded Radius (inch)	21.5
Rolling Circumference (inch)	139
Rim Rec	13 SDC
Rim Alt	12
ECE	E11-106R-003641

## Load capacity (lbs)

mph / psi	65
25 DW	9370
30 DW	9090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 08/11/2024 09:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..