



RIDEMAX IT 696 - Data Sheet



Description

RIDEMAX IT 696 has a unique tread design and a wide footprint that provides excellent grip for road applications, even in winter conditions. The tire is best suitable for transport and municipality/maintenance applications thanks to its high-speed feature and strong casing. The tread design has been specifically developed for heavy-duty services and ensures a low rolling resistance that provides fuel economy plus great stability.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	TMPH	ECE
240/70 R 16 IND	STANDARD	94067503	107A8/107B	W8	W9	9.6	29.2	13.5	87.6	TL	0	E11-106R-006942
340/80 R 18 IND	STANDARD	94048960	143 A8/138 D	11 ; 11 SDC ; W 11	W 10 ; 12 ; 12 SDC	13.5	39.4	18	117.3	TL	0	E11-106R-002987
360/80 R 20 IND	STANDARD	94071074	143D/147A8	11	W 10 ; W 11 ; 12 ; W 12	14.1	42.7	19.2	127.4	TL	0	E11-106R-007845
300/80 R 24 IND (11.2 R 24)	STANDARD	94033881	133 A8/128 D	DW 10		11.6	42.9	19.7	129.8	TL	0	E4-106R-002292
340/80 R 24 IND (12.4 R 24)	STANDARD	94033843	140 A8/135 D	DW 11	W 10 ; W 12 ; DW 10	13.5	45.4	20.5	135.6	TL	0	E4-106R-002293
360/80 R 24 IND (13.6 R 24)	STANDARD	94057252	143 A8/138 D	DW 11	W 12 ; W 10	13.5	46.7	21.1	140	TL	0	E11-106R-004753
400/80 R 24 IND (14.9 R 24)	STANDARD	94038640	149 A8/144 D	DW 13	W 12 ; W 14 L	15.9	49.2	22	148	TL	0	E4-106R-002400
420/65 R 24 IND	STANDARD	94058464	146 D/151 A8	DW 13 L ; W13	DW 15 L ; DW 14 L	16.5	45.6	20.9	137.1	TL	1	E11-106R-005952
440/80 R 24 IND (16.9 R 24)	STANDARD	94057269	154 A8/149 D	DW 14 L	DW 15 L ; DW 13	17.4	51.7	23.2	155.1	TL	0	E11-106R-004760
460/65 R 24 IND	STANDARD	94058655	151 D/156 A8	DW 14 L	DW 15 L ; DW 13	17.9	47.8	21.6	143.5	TL	1	
500/70 R 24 IND	STANDARD	94070244	164A8/159D	DW 16 L	DW 15 L ; DW 18 L	19.8	51.6	23.7	155.7	TL	0	E11-106R-007547
500/70 R 24 IND	STANDARD	94067862	157 A8/152 D	DW 16 L	DW 15 L ; DW 18 L	19.8	51.6	23.7	155.7	TL	0	E11-106R-007051
400/80 R 28 IND (14.9 R 28)	STANDARD	94039227	151 A8/146 D	W 13	W 12 ; W 14 L	15.9	53.2	24.2	159.4	TL	0	E4-106R-002401
440/80 R 28 IND (16.9 R 28)	STANDARD	94034895	156 A8/151 D	W 14 L	W 15 L	17.4	55.7	25	168.8	TL	0	E4-106R-002299
440/80 R 30 IND (16.9 R 30)	STANDARD	94035816	157 A8/153 D	W 14 L	W 15 L	17.4	57.7	26.3	175.4	TL	0	E4-106R-002297
480/80 R 30 IND (18.4 R 30)	STANDARD	94033850	162 A8/157 D	W 15 L	W 16 L	18.9	60.2	26.5	179.4	TL	0	E4-106R-002298
440/80 R 34 IND (16.9 R 34)	STANDARD	94038657	159 A8/155 D	DW 14 L	DW 15 L ; DW 16 L	17.4	61.7	27.7	188	TL	0	E4-106R-002295
480/80 R 34 IND (18.4 R 34)	STANDARD	94035106	164 A8/159 D	W 15 L	W 16 L	18.9	64.3	28.7	192.7	TL	0	E4-106R-002296
480/80 R 38 IND (18.4 R 38)	STANDARD	94033867	166 A8/161 D	W 15 L	W 16 L	18.9	68.2	30.7	205.2	TL	0	E11-106R-004075
540/80 R 38 IND	STANDARD	94055838	172 A8/167 D	W 18 L	W 16 L	21.7	72	32.8	218	TL	0	E11-106R-004077
540/80 R 42 IND	STANDARD	94062409	168 D/173 A8	W 18 L	W 16 L	22	76	34.6	231.3	TL	0	E11-106R-005714

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..