

## TR 391 - Technical Specifications



### Description

TR 391 is an agro-industrial tire suitable for transport and compacting operations with sugar cane trailers and compactors. TR 391 features high load capacity and a longer service life.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Trailer  
Industrial: Compactor

Version	STANDARD
Type	TL
Tyre Size	14.9 - 24
LI/SS	123 A6

## Dimensions International Standard

Ply Rating	6
Section Width (mm)	405
Overall Diameter (mm)	1270
Static Loaded Radius (mm)	574
Rolling Circumference (mm)	3805
SRI (mm)	600
Rim Rec	DW 13
Rim Alt	DW 11 ; DW 13 L ; DW 12
TRA Code	R3

## Load capacity (Kg)

km/h / bar	1.40
30	1550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 08/11/2024 13:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..