

VIJETA - Technical Specifications



Description

VIJETA is an agricultural tire suitable for both on- and off-the-road applications. The 5-rib pattern optimizes load distribution. In addition, the wear-resistant compound and the strong casing stand for a long tire life-cycle.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Trailer

Version	STANDARD
Type	TT
Tyre Size	7.00 - 19

Dimensions International Standard

Ply Rating	10
Section Width (mm)	195
Overall Diameter (mm)	852
Rim Rec	5.00
ECE	E11-106R-004106

Load capacity (Kg)

km/h / bar	5.15
15	1360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 08/11/2024 13:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..