

# XL GRIP IND3 (ECH) - Data Sheet



## **Description**

XL GRIP (IND-3) is a bias-ply tire for empty container handlers in stacking and lifting applications. The tire features a strong casing, which provides great durability and as well as a high stability in lift mode.

### **UM**

**US Standard** 

#### Construction

BIAS

## Machinery

Industrial: Empty Container Handler

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Туре
12.00 - 24	INDUSTRIAL	94032785	IND3	24	8.5	8.0	12.6	49.2	23	146.1	TT
16.00 - 25	INDUSTRIAL	94031894	IND3	28	11.25/2.0	13.00/2.0	18.3	58.5	26.9	173	TL
18.00 - 25	PORT INDUSTRIAL	94049035	IND3	32	13.00/2.5	15.00/2.5	20.1	63.6	29.1	188.2	TL
18.00 - 25	PORT INDUSTRIAL	94049042	IND3	40	13.00/2.5	15.00/2.5	20.1	63.6	29.1	188.2	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

#### Printed on 08/11/2024 11:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..