

XL GRIP IND3 (RTG) - Data Sheet



Description

XL GRIP (IND-3) is a bias-ply tire for RTG cranes in stacking and lifting applications. The tire features a strong casing made of a specially formulated tread compound, which provides an extended tire life-cycle.

UM

US Standard

Construction



Machinery

Industrial: RTG Crane

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	ow	OD	SLR	RC	Туре
16.00 - 25	INDUSTRIAL	94031900	IND3	32	11.25/2.0	13.00/2.0	18.3	58.5	26.9	173	TL
18.00 - 25	INDUSTRIAL	94015931	IND3	40	13.00/2.5	15.00/2.5	20.1	63.6	29.1	188.2	TL
18.00 - 25	INDUSTRIAL	94034642	IND3	32	13.00/2.5	15.00/2.5	20.1	63.6	29.1	188.2	TL
21.00 - 25	INDUSTRIAL	94027316	IND3	32	15.00/3.0	17.00/3.0	22.7	68.9	31.1	204.1	TL
21.00 - 25	INDUSTRIAL	94028184	IND3	36	15.00/3.0	17.00/3.0	22.7	68.9	31.1	204.1	TL
21.00 - 25	INDUSTRIAL	94026708	IND3	40	15.00/3.0	17.00/3.0	22.7	68.9	31.1	204.1	TL
21.00 - 25	INDUSTRIAL	94063840	IND3	44	15.00/3.0	17.00/3.0	22.7	68.9	31.1	204.1	TL
24.00 - 29	INDUSTRIAL	94041343	IND3	42	17.00/3.5		25.8	78.5	35.4	230.7	TL
21.00 - 35	INDUSTRIAL	94043309	IND3	36	15.00/3.0		22.8	79.5	36.5	235.4	TL
21.00 - 35	INDUSTRIAL	94043361	IND3	40	15.00/3.0		22.8	79.5	36.5	235.4	TL
24.00 - 35	INDUSTRIAL	94039562	IND3	48	17.00/3.5		25.8	83.9	38.4	248.1	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 08/11/2024 09:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..